



FR\_30CON



FR\_24CON



FR\_15CON



FR\_18.2CON



FR\_24.2CON



### CONSTRUCTION

1. The Frio Series Concrete Planters are cast with a minimum wall thickness of 3 inches. Planters have an average strength tested at 28-30 days of 5,810 psi.
2. Planters are lightly sanded and sealed, inside and outside, to enhance color and protect surfaces from moisture, dirt, and stains.
3. Planters are manufactured with standard 1", 1.5", or 2" drain holes or no drain holes. Quantity and placement as directed by Purchaser .
4. Holes are cast into planter using standard PVC pipe trade sizes. Holes cannot be added after casting as doing so will void unit warranty.
5. Custom sizes are not available.

### SURFACE FINISH

1. Planters will have a naturally pitted surface finish. (Reference Manufacturer's Concrete Finish Sheet)

### CONCRETE COLOR SELECTION

1. Planters are offered in a standard gray (no pigment), or select integral color pigments. (Reference Manufacturer's Concrete Finish Sheet)
2. Premium colors are additional, including blues, greens, and graphite black.

### FRIO SERIES CONCRETE STANDARD SIZES

PRODUCT ID	DIAMETER	HEIGHT	THICKNESS	AVG. WT.
FR_30CON	30"	30"	3 IN.	870 lbs
FR_24.2CON	24"	24"	3 IN.	530 lbs
FR_24CON	36"	24"	3 IN.	920 lbs
FR_18.2CON	28"	18"	3 IN.	510 lbs
FR_15CON	48"	15"	3 IN.	985 lbs