



CONSTRUCTION

1. The Frio Series Aluminum Powder Coated Planters are constructed of ASTM B-209 5052-H32 grade Aluminum. Planters are fabricated using a .125 thickness.
2. Planters are coated with an exterior grade polyester powder coat finish, available in standard stock and non-standard stock RAL colors. Marine grade finish can be provided for an upcharge per unit.
3. Planters are manufactured with standard 1", 1.5", or 2" drain holes or no drain holes. Quantity and placement as directed by Purchaser. Holes are cut to nominal O.D. for standard PVC pipe trade sizes.

STANDARD SELECTIONS

1. Standard lip = 2" wide lip with no return.
2. Standard toe-kick = 2" H x 2" inset.

CUSTOMIZATION

1. Fabrication of F&F Aluminum Powder Coated Frio Series can be customized to designer specified sizes for DIAM. X H. Custom size units will be priced on labor, material, and thickness.
2. Flat base, no toe-kick.

POWDER COAT FINISH

(Reference Form & Fiber Metal Finishes sheet)



FRIO SERIES ALUMINUM STANDARD POWDER COATED SIZES

PRODUCT ID	TOP O.D.	HEIGHT	THICKNESS	AVG. WT.
FR_42A	26"	42"	0.125	51 lbs
FR_30A	30"	30"	0.125	46 lbs
FR_24A	36"	24"	0.125	50 lbs
FR_18A	60"	18"	0.125	83 lbs
FR_18.2A	28"	18"	0.125	30 lbs
FR_24.2A	24"	24"	0.125	30 lbs