



CONSTRUCTION

1. The Cypress Series Concrete Planters are cast with a minimum wall thickness of 3 inches. Planters have an average strength tested at 28-30 days of 5,810 psi.
2. Planters are lightly sanded and sealed, inside and outside, to enhance color and protect surfaces from moisture, dirt, and stains.
3. Planters are manufactured with standard 1", 1.5", or 2" drain holes or no drain holes. Quantity and placement as directed by Purchaser .
4. Holes are cast into planter using standard PVC pipe trade sizes. Holes cannot be added after casting as doing so will void unit warranty.
5. Custom sizes are not available.

SURFACE FINISH

1. Planters will have a naturally pitted surface finish. (*Reference Manufacturer's Concrete Finish Sheet*)

CONCRETE COLOR SELECTION

1. Planters are offered in a standard gray (no pigment), or select integral color pigments. (*Reference Manufacturer's Concrete Finish Sheet*)
2. Premium colors are additional, including blues, greens, and graphite black.

CYPRESS SERIES CONCRETE  
STANDARD SIZES

PRODUCT ID	TOP O.D.	HEIGHT	BASE O.D.	THICKNESS	AVG. WT.
CY_40CON	26"	40"	16"	3 IN.	680 lbs
CY_26CON	36"	26"	18"	3 IN.	680 lbs
CY_22CON	30"	22"	15"	3 IN.	472 lbs
CY_18CON	42"	18"	26"	3 IN.	578 lbs
CY_15CON	22"	15"	10"	3 IN.	175 lbs
CY_15.2CON	30"	15"	15"	3 IN.	365 lbs